

FEATURE

- Interchangeable Digital Sensor Probes.
- Thermistor Sensor For Temperature Measurement, Fast Response Time
- Dual Display.
- Dew Point Measurement.
- PC Interface.
- 16,000 Records Data Logger.
- Auto Shut Off For Battery Saving.
- Extendable Cable.
- Tilt Stand.



SPECIFICATIONS

Sensor:

Electronic capacitance polymer film sensor/NTC

Measurement Range:

Temperature: -20°C~60°C ; -4°F~140°F

Humidity: 0%RH~100%RH

Resolution: 0.1°C/0.1°F/0.1%RH

Accuracy:

Temperature: ±0.8°C, ±1.5°F

Humidity: ±2.0%RH

Response Time: (@t90; in slowly moving air)

Humidity: 180 sec.

Temperature: 10sec.

Display: LCD, 2 lines.

Parameters Displayed:

Relative humidity, temperature and dew point.

Battery Type: 9V battery

Battery Lifetime: Approx. 80 hours

Dimensions:

Meter: 185(L)×65(W)×36(H)mm

Probe: 94(L)×15mm Dia

Weight: Approx. 285g

Accessories:

9V Battery, Instruction Manual, Windows software, USB Cable, RS-232 Cable(Optional), Carry Case, AC Adapter(Optional).



33%RH / 75%RH
Humidity Standard (OPTIONAL)



LED Back Light



* The specifications and other information in this catalogue are subject to change without prior notice.

CENTER®

CENTER TECHNOLOGY CORP.

4/F., NO.415, Jung-Jeng Rd., 238 Shu-Lin, Taipei, Taiwan
 TEL: 886-2-26763926 E-Mail: center@centertek.com
 FAX: 886-2-26763925 http://www.centertek.com

Distributed by: