




TM-201 Light Meter

Display :

- 3¹/₂ digits LCD with maximum reading 2000.
- Overload indication : "OL" .
- Low battery indication : "  ".

Specifications :

Measuring range	200, 2000, 20000, 200000 Lux 20,200, 2000, 20000 Foot-candle	
Accuracy	±3% (Calibrated to standard incandescent lamp 2856°K) ±8% (other visible light source)	
Angle deviation from cosine characteristics	10° 30° 50° 60° 80°	±0.5% ±2% ±3% ±6% ±25%

- Data hold.
- Max.hold.
- Zero adjustment.
- Sensor : Silicon photo diode and filter.
- Meter size : 130x56x38mm. (LxWxH)
- Sensor size : 80x56x25mm. (LxWxH)
- Weight : 250g.

- According to JISC1609 : 1993 and CNS 5119 general A class specifications.
- Spectral response close to CIE luminous spectral efficiency.
- Measuring intensities of illumination in Lux or Foot-candle.
- Silicon photo diode and filter.
- Measuring light source include all visible light source.
- Length of wire for light sensor : approximately 1.5M.
- Cosine angular corrected.
- Applications include : warehouses, factories, office buildings, restaurants,schools, library, hospitals, photographic, video, parkinggarages, museums, art galleries, stadiums, building security.

TM-202 Light Meter



Functions :

- Data hold.
- DC analog output.
- Max / Min hold.
- Zero adjustment.
- Sensor : Silicon photo diode and filter.
- Meter size (LxWxH) : 130x56x38mm.
- Sensor size (LxWxH) : 80x56x25mm.
- Accuracy : 250g.

Measuring range	20,200, 2000, 20000, 200000 Lux 20,200, 2000, 20000 Foot-candle	
Accuracy	±3% (Calibrated to standard incandescent lamp 2856°K) ±6% (other visible light source)	
Angle deviation from cosine characteristics	10° 30° 50° 60° 80°	±0.5% ±2% ±3% ±6% ±25%

TM-720 Mini Pocket Light Meter



Display :

- 3³/₄ digits LCD with maximum reading 3999.
- Overload indication : "OL" .
- Low battery indication : "  ".

Featuers :

- According to JISC1609 : 1993 and CNS 5119 general A class specifications.
- Spectral response close to CIE luminous spectral efficiency.
- Measuring intensities of illumination in unit of Lux or Foot-candle.
- Silicon photo diode and filter.
- Measuring light source include all visible light source.
- Cosine angular corrected.
- Auto power off with disable function.
- Data hold.
- Max/Min/AVG hold.
- Real Zero function.
- Auto ranging.
- Many applications include: warehouses, factories, office buildings, restaurants, schools, library, hospitals, photographic, video, parking garages, museums, art galleries, stadiums, building security.

Specifications :

Accuracy	±3% ±3Lux (0~500Lux) 3% (up 501 Lux) (Calibrated to standard incandescent lamp 2856°K) ±8% (other visible light source)	Measuring range	40/400/4,000/40,000/400,000 Lux 40/400/4,000/40,000 Foot-candel
		• Meter size (LxWxH) : 133 x48 x23mm	
		• Power : 2 batteries 1.5V AAA	
		• Weight (including battery) : 80g	