

3399F



Drain/pipe Inspection Camera System with 40m, 50m or 60m (131, 164 or 197ft) cable

Camera Head

Material	#304 Stainless Steel	Cable dia. 6.8mm(0.27")
Dimension	Φ38mmx81mm(Main body)	Cable length: 40/50/60m for option
sensor	1/3" Sony CCD, 480 TV Lines	
ViewAngle	120°	
Focal Distance	12-120cm	
LEDs	12pcs high light LEDs	
Waterproof	Max. 20m under water	
Two Roller Skids, Mini one at dia. 72mm another universal skid at dia. 115-250mm		
Built-in 512Hz Sonde(optional)		
With self-leveling feature		

Monitor

7" LCD color TFT LCD
With universal installation brackets
SD Card slot to store still pictures or videos
One push record button
Built-in rechargeable battery lasts up to 5 hours
On-Screen date and time
On-Screen meter/ft. distance display



Keyboard for Text Input

Stand Horizontally

Specifications

Camera Head

Material	#304 Stainless Steel
Dimension	Φ38mmx81mm(Main body)
sensor	1/3" Sony CCD, 480 TV Lines
View Angle	120°
Focal Distance	12-120cm
LEDs	12pcs high light LEDs
Waterproof	Max. 20m(65') under water

Monitor

LCD	7" 16:9 high definition color LCD monitor
Resolution	800x480 R.G.B
Encoding	H. 264
Storage	SD Card slot to store still images or videos
Sound	Local audio recording
Battery	Built-in rechargeable battery
Work time	4-5 hours
Charge time	6-7 hours
Menu Language	English, German, French, Spanish, Italian, Chinese, Japanese, Russian, Portuguese.

Push Cable

Cable dia. 6.8mm	Fiberglass
Cable Material	40/50/60m(131/164/197ft)
Available Length	Stainless Steel
Wheel Material	



3399FB with monitor and keyboard mounted in a rain resistant box

See price list for complete list of different options, part numbers, spare parts and prices.
ALL PRODUCTS, PRODUCT SPECIFICATIONS AND DATA ARE SUBJECT TO CHANGE WITHOUT NOTICE TO IMPROVE RELIABILITY, FUNCTION OR DESIGN OR OTHERWISE