



2310 SL

FEATURES

- Max. & Min. function.
- Over & Under range indication.
- 4-digit LCD display with bar graph.
- Frequency weighting characteristic for 2 times per second.
- AC signal output.
- Low battery indication.
- IEC 651 Type 2 & ANSI S1.4 Type 2.

SPECIFICATIONS

Measuring Ranges	Lo : 32dB~80dB Med : 50dB~100dB Hi 80dB~130dB
Accuracy	±1.5dB (at Reference Range)
Reference sound level & frequency	94dB , 1kHz
Resolution	0.1dB
Detector-Indicator characteristic	Fast : 125mS Slow : 1 S
Analog signal output	AC 1Vrms for each range
Dimensions	235(L) x 58.4(W) x 34(D)mm
Weight(prox)	220g(battery included)
Power source	9V(6F22.006p)x1 battery
Accessories	Instruction manual Adjusting bar Battery Sponge cover



2330 LX

FEATURES

- Wide range for measurements as high as 40000 lux and 4000 fc.
- 0.01 lux and 0.001 fc resolution for accurate low light level measurements.
- Light sensor cover is included for preserving sensor life.
- Auto off function.
- Data hold and peak hold function.
- Low battery indication.
- Over range indication.
- Auto-ranged.
- Manual-ranged.
- Calibration mode is provided.
- 9V battery system.
- Selection key for lux and fc.
- The spectral sensitivity close to CIE photopic curve.
- Ideal tool for workplace, clean-room and computer room light testing.
- Video, photographic, office, classroom, and architectural uses.

SPECIFICATIONS

Measuring Ranges	39.99 / 399.9 / 3999 / 39999 lx 3.999 / 39.99 / 399.9 / 3999fc
Resolution	0.01 lx - 10 lx 0.001 fc - 1 fc
Accuracy	±(3%rdg+5dgt) Calibrated to standard Incandescent lamp, 2856°K.
Display	40000 - conut LCD
Photosensor	Silicon photodiode
Operating / Storage conditlions	0°C - 40°C < 80% RH -10°C - 50°C < 70% RH
Power source	9V(6F22.006p)x1 battery
Dimensions	194(L) x 62(W) x 34(D)mm
Weight(prox)	245g(battery is included)
Accessories	Instruction manual Battery Carry case