

Pocket-sized Clamp Meter

Clamp Meters

Insulation Testers/Earth Tester

Digital Multimeters

Analog Multitesters

Automotive Testers

Other Testers

Accessories



AC 300A DISP HOLD APO

SK-7601

FEATURES

- Simple operation.
- Strong and beaked Clamp Head against twists.
- AUTO POWER OFF : turns off automatically after 12 minutes.
- Full Auto Ranging up to 300A AC.
- DISPLAY HOLD Function.
- With Carrying Case.

OPTIONAL ACCESSORY

880 Line Separator

SPECIFICATIONS

Display : 4000 count LCD,  
Maximum reading 4000  
Sampling Rate : 2.5 times / sec  
Range Selection : Auto Ranging  
Conductor Diameter :  $\phi$  27mm Max.  
Power Supply : 3V CR2032 Battery (x 1)  
CE Mark : CAT III 300V and EMC  
Dimensions : 150(H) x 52(W) x 24(D)mm  
Weight : 110g  
Accessories : 1004 Carrying Case (x 1)  
3V CR2032 Battery (x 1)

	Range	Accuracy
AC Current	40A	$\pm 1.5\% \text{rdg} \pm 5 \text{dgt}$
	300A	$\pm 1.8\% \text{rdg} \pm 5 \text{dgt}$
Functions	Display Hold, Auto Power OFF	

Multi-functional Handy Clamp with Long Battery Life



AC 400A ACDC V  $\Omega$  Hz  $\rightarrow$  DUTY %  $\rightarrow$   
MAX MIN DIFF DISP HOLD APO TRUE RMS

SK-7602 TRUE RMS

FEATURES

- 220-hours long time measurement. (with alkaline cells)
- 13 measurement functions in one small package.
- Rubber-molded rotary switch and trigger.
- Easy-to-clamp compact & beaked clamp head even for narrow conductors.
- True RMS, MAX/MIN and Difference measurement.

SPECIFICATIONS

Display : 4000 count LCD, Maximum reading 4050  
Sampling Rate : 3 times / sec  
Range Selection : Auto Ranging  
Conductor Diameter :  $\phi$  27mm Max.  
Power Supply : 1.5V R03 or AAA Batteries (x 2)  
CE Mark : CAT III 300V, CAT II 600V and EMC  
Dimensions : 171(H) x 58(W) x 27(D)mm  
Weight : 140g  
Accessories : 100-63 Test Leads (x 1 set)  
1015 Carrying Case (x 1)  
1.5V R03 Batteries (x 2)

	Range	Accuracy
$\sim$ / Hz	AC Current	40A $\pm 1.5\% \text{rdg} \pm 5 \text{dgt}$ (50Hz/60Hz) 400A $\pm 3.0\% \text{rdg} \pm 5 \text{dgt}$ (40Hz to 400Hz)
	Frequency	5Hz to 1kHz $\pm 0.2\% \text{rdg} \pm 2 \text{dgt}$ 400mV $\pm 1.0\% \text{rdg} \pm 3 \text{dgt}$
$\nabla$ / $\nabla$	DC Voltage	4V 40V 400V 600V $\pm 1.0\% \text{rdg} \pm 2 \text{dgt}$
	AC Voltage	4V 40V 400V 600V $\pm 1.5\% \text{rdg} \pm 5 \text{dgt}$ (40Hz to 400Hz)
Hz / %	Frequency	5Hz to 49.99kHz $\pm 0.2\% \text{rdg} \pm 2 \text{dgt}$
	Duty Cycle	5% to 95% $\pm 2.0\% \text{rdg} \pm 3 \text{dgt}$ $\pm 1.5\% \text{rdg} \pm 5 \text{dgt}$
Resistance	400 $\Omega$	$\pm 1.5\% \text{rdg} \pm 5 \text{dgt}$
	4k $\Omega$	$\pm 0.7\% \text{rdg} \pm 3 \text{dgt}$
	40k $\Omega$	$\pm 0.7\% \text{rdg} \pm 3 \text{dgt}$
	400k $\Omega$	$\pm 0.7\% \text{rdg} \pm 3 \text{dgt}$
	4M $\Omega$	$\pm 1.2\% \text{rdg} \pm 5 \text{dgt}$
Other Measurements	40M $\Omega$	$\pm 3.0\% \text{rdg} \pm 5 \text{dgt}$
	Continuity Test, Diode Test, Capacitance	
Functions	MAX / MIN, Difference, Display Hold, Auto Power OFF	


OPTIONAL ACCESSORIES

880 Line Separator  
940 Alligator Clips  
948 Alligator Clips  
793 Coil-Type Contact Pin

Easy & Useful

Easy - to - Clamp

SK-7602's compact and beaked clamp heads assure easy clamping even for narrow conductors.



$\phi$  27mm MAX

Avoid Your Fingers Slips

SK-7602 are always fit on your hand. Double-Molding Rubbers on a Function Switch and a Trigger avoid your fingers slips during operation.



Test Lead Holder

Fixable Test Lead on the side of SK-7602 by inserting its hook into the holder socket. Useful for Voltage, Resistance, Capacitance Measurements, Continuity and Diode Tests.

